

Adaptation

The hydrophilic coated guidewire with special coating formula is widely used in both diagnosis and treatment of interventional therapies.

It has good support yet right control to ensure device delivery through tortuous anatomy.


Features

- Advanced hydrophilic coating to provide lasting lubrication.
- Soft atraumatic tip provides flexibility and minimizes trauma.
- The NT core provides 1:1 torque control, perfect combination of support and maneuverability in tortuous anatomy. Enhanced visualization for accurate positioning.
- Complete range of specification to accommodate physician preference.

Ordering Information

No.	Catalog number	Diameter (inch)	Length (cm)	Tip	Hardness Type
1	GWO-18-120A	0.018	120	Angled	Normal
2	GWO-18-150A		150		
3	GWO-18-180A		180		
4	GWO-18-220A		220		
5	GWO-18-260A		260		
6	GWO-18-120S		120	Straight	
7	GWO-18-150S		150		
8	GWO-18-180S		180		
9	GWO-18-220S		220		
10	GWO-18-260S		260		
11	GWO-18-150SM		150		
12	GWO-18-200SM		200		
13	GWO-18-300SM		300		
14	GWO-21-120A	0.021	120	Angled	
15	GWO-21-150A		150		
16	GWO-21-180A		180		
17	GWO-21-220A		220		
18	GWO-21-260A		260		
19	GWO-21-120S		120	Straight	
20	GWO-21-150S		150		
21	GWO-21-180S		180		
22	GWO-21-220S		220		
23	GWO-21-260S		260		
24	GWO-25-050A	0.025	50		
25	GWO-25-080A		80		
26	GWO-25-120A		120		
27	GWO-25-150A		150		
28	GWO-25-180A		180		
29	GWO-25-220A		220		
30	GWO-25-260A		260		
31	GWO-25-050S		50	Straight	
32	GWO-25-080S		80		
33	GWO-25-120S		120		
34	GWO-25-150S		150		
35	GWO-25-180S		180		
36	GWO-25-220S		220		
37	GWO-25-260S		260		
38	GWO-32-050A	0.032	50	Angled	
39	GWO-32-080A		80		
40	GWO-32-120A		120		
41	GWO-32-150A		150		

Models Naming Composition



E.g. Model No.GWO-35-150A represents guidewire OD of 0.035 inch, 150cm in length, with angled tip.


- Commonly used models, recommend to stock up regularly.
- Less commonly used models, recommend to stock up moderately.

Note: 0.01 inch = 0.254 mm

Ordering Information

No.	Catalog number	Diameter (inch)	Length (cm)	Tip	Hardness Type
42	GWO-32-180A	0.032	180	Angled	Normal
43	GWO-32-220A		220		
44	GWO-32-260A		260		
45	GWO-32-050S		50	Straight	
46	GWO-32-080S		80		
47	GWO-32-120S		120		
48	GWO-32-150S		150		
49	GWO-32-180S		180		
50	GWO-32-220S		220		
51	GWO-32-260S		260		
52	GWO-35-050A	0.035	50	Angled	Normal
53	GWO-35-080A		80		
54	GWO-35-120A		120		
55	GWO-35-150A		150		
56	GWO-35-180A		180		
57	GWO-35-220A		220		
58	GWO-35-260A		260		
59	GWO-35-050S		50	Straight	
60	GWO-35-080S		80		
61	GWO-35-120S		120		
62	GWO-35-150S	150			
63	GWO-35-180S	180			
64	GWO-35-220S	220			
65	GWO-35-260S	260			
66	GWO-38-050A	0.038	50	Angled	Normal
67	GWO-38-080A		80		
68	GWO-38-120A		120		
69	GWO-38-150A		150		
70	GWO-38-180A		180		
71	GWO-38-220A		220		
72	GWO-38-260A		260		
73	GWO-38-050S		50	Straight	
74	GWO-38-080S		80		
75	GWO-38-120S		120		
76	GWO-38-150S	150			
77	GWO-38-180S	180			
78	GWO-38-220S	220			
79	GWO-38-260S	260			
80	GWH-25-150A	0.025	150	Angled	Hardened
81	GWH-25-180A		180		
82	GWH-25-220A		220		

Models Naming Composition



E.g. Model
No.GWO-35-150A
represents guidewire OD of 0.035 inch, 150cm in length, with angled tip.


- Commonly used models, recommend to stock up regularly.
- Less commonly used models, recommend to stock up moderately.

Note: 0.01 inch = 0.254 mm

Ordering Information

No.	Catalog number	Diameter (inch)	Length (cm)	Tip	Hardness Type
83	GWH-25-260A	0.025	260	Angled	Hardened
84	GWH-25-150S		150	Straight	
85	GWH-25-180S		180		
86	GWH-25-220S		220		
87	GWH-25-260S		260		
88	GWH-32-150A	0.032	150	Angled	
89	GWH-32-180A		180		
90	GWH-32-220A		220		
91	GWH-32-260A		260		
92	GWH-32-150S		150	Straight	
93	GWH-32-180S	180			
94	GWH-32-220S	220			
95	GWH-32-260S	260			
96	GWH-35-150A	0.035	150		Angled
97	GWH-35-180A		180		
98	GWH-35-220A		220		
99	GWH-35-260A		260		
100	GWH-35-150S		150	Straight	
101	GWH-35-180S	180			
102	GWH-35-220S	220			
103	GWH-35-260S	260			
104	GWH-38-150A	0.038	150		Angled
105	GWH-38-180A		180		
106	GWH-38-220A		220		
107	GWH-38-260A		260		
108	GWH-38-150S		150	Straight	
109	GWH-38-180S	180			
110	GWH-38-220S	220			
111	GWH-38-260S	260			

Models Naming Composition



E.g. Model
No.GWO-35-150A
 represents guidewire OD of 0.035 inch, 150cm in length, with angled tip.

- Commonly used models, recommend to stock up regularly.
- Less commonly used models, recommend to stock up moderately.

Note: 0.01 inch = 0.254 mm